







Mondrian® Plus 80 Paver




-  Pedestrian - Designed to withstand pedestrian traffic
 -  Vehicular - Designed to withstand car traffic
 -  Permeable - Designed to allow runoff to pass through
-  1 bag of sand covers approx. 43 ft²


Mondrian® Plus 80 Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW	
A	A	80 x 165 x 330	3 1/8 x 6 1/2 x 13	PRESTIGE COLOURS		
	B	80 x 330 x 330	3 1/8 x 13 x 13	10551159 Range Margaux Beige		
B	C	80 x 330 x 495	3 1/8 x 13 x 19 1/2	10551158 Range Amboise Beige		
	Weight/unit (avg.)	18 kg	40 lb	10550461 Range Scandina Grey		
C	Unit/surface (avg.)	9.17 unit/m ²	0.85 unit/ft ²	STANDARD COLOURS		
	Area/layer	0.98 m ²	10.55 ft ²	10551156 Range Norvick Grey		
	Area/cube	8.82 m²	9 Rows	94.95 ft²		10551160 Range Newport Grey
	Qty/cube	A = 36	B = 36	C = 18		Sold by layer
	Length/row	2.97 lin. m	9.75 lin. ft			Can be double stacked
	Length/cube	26.73 lin. m	87.75 lin. ft			Production location St-Eustache, Québec and Metcalfe
	Weight/cube	1680 kg	3704 lb			

LAYING PATTERNS



Linear



Modular

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 80 Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).